




TRACTOR REQUIREMENT: 35 HP AND ABOVE

MODEL '2440-S' SUPER SOD SCALPER WITH SUBSOILER
FOR SOD REMOVAL AND SUBSOILING •

SPECIFICATIONS FOR THE MODEL 2440 SCALPER PART OF UNIT

HITCH	CATEGORY # II & III THREE POINT HITCH · SEVEN POSITIONS
COULTER ASSEMBLY	3/8 X 18" HI-CARBON STEEL BLADE 4-LUG HEAVY DUTY HUB WITH REPLACEABLE SEALED BEARINGS
SCALPER FROG	HI-CARBON CASE-HARDENED STEEL · REPLACEABLE CUTTING EDGE ADJUSTABLE CUTTING DEPTH CONTROL
DISC HUBS & COMPONENTS	3/16" X 20" DISHED DISCS · HEAVY DUTY SPINDLES · 6-LUG HUB WITH REPLACEABLE SEALED BEARINGS
MISCELLANEOUS	REAR HI-CARBON STEEL ADJUSTABLE DEPTH CONTROL SKID
	MODEL S-39 BREAK AWAY SUBSOILER • DO IT ALL IN ONE PASS: SUBSOILER FOOT IS OFFSET SIX (6) INCHES SO THAT CENTER OF PLOW CAN BE USED FOR TRANSPLANTING THE TREE SEEDLINGS SUBSOILS DEPTH OF EIGHTEEN (18) INCHES

2440 ONLY



PRICE: \$ 7,685.00 F.O.B. MABLETON, GEORGIA ♦ USA