




TRACTOR REQUIREMENT: 30 HP AND ABOVE

**MODEL '5200 TOWABLE · MEDIUM TO HEAVY DUTY**  
**· TWO SEAT PLANTER**  
**2" REMOVABLE TRAILER HITCH · HITCH JACK**

HITCH	TOW RING TO TRACTOR DRAWBAR · CHOOSE EITHER 'MANUAL' HAND PUMP ON BOARD' <i>OR</i> TRACTOR HYDRAULIC ASSIST TO RAISE OR LOWER COULTER & TRENCHER FOOT · BOTH OPERATED BY PLANTER OPERATOR
MAIN BEAM	3/4" BOXED BEAM · ADJUSTABLE COULTER ARMS · <u>NO DEPTH SKIDS</u> · WEIGHT BRACKETS SUPPLIED FOR FOUR 100-POUND WEIGHTS · <u>WEIGHTS NOT INCLUDED · USE TRACTOR SACHEL WEIGHTS</u>
COULTER ASSEMBLY	3/8 X 26" HI-CARBON STEEL BLADE 4-LUG HEAVY DUTY HUB WITH REPLACEABLE SEALED BEARINGS
FOOT	2" HI-CARBON STEEL TRENCHER FOOT – CHANGEABLE PIN-TYPE POINT ONE SET TRENCHER PLATES – YOUR CHOICE OF SIZE
PACKING WHEEL ASSEMBLY	12" FOAM FILLED PACKING TIRES · ADJUSTABLE PACKING SPINDLES · HEAVY DUTY 4-LUG HUBS · TIMKEN HIGH-SPEED WHEEL BEARINGS · EQUIPPED WITH OUR PATENTED <i>GUMBO SOIL FOLD BRACKET</i>
SEEDLING BOXES	TWO LARGE CAPACITY REMOVABLE BOXES · WITH DRAIN PLUGS
OPERATOR USE	TWO HI-BACK COMFORT SEATS · ADJUSTABLE SEAT BRACKET GROUND CLEARANCE – 36" · PROTECTIVE FOOT REST & LEG PROTECTORS · SAFETY HAND HOLD RODS
OPTIONAL ITEMS AVAILABLE	26" OR 32" SCALPERS ♦ SEEDLING DISTANCE FINDER
MISCELLANEOUS	PAINTED HI-GLOSS SAFETY ORANGE · CARRIER TIRES · 6-LUG 700 x 15 TRUCK TIRES · TIMKEN EQUIPPED
	INFORMATION FOR FLATBED TRUCK SHIPPING: UNIT 8'10" LONG X 54" WIDE X 5'2" HIGH WEIGHT: APPROXIMATELY 1800 LB. PRICE: \$ 10,680.00 F.O.B. MABLETON, GEORGIA ♦ USA