

**MODEL 'SC' SINGLE CRANK AXLE ONLY**  
**FOR FLAT OR CONTOUR LAND UP TO 15% SLOPE**  
**OPERATES WITH ONE HYDRAULIC CYLINDER · (NOT SHOWN)**  
**PRICE: \$ 8,590.00 F.O.B. MABLETON, GEORGIA ♦ USA**  
**(SHOWN BELOW)**

**MODEL 'DC' DOUBLE CRANK AXLE ONLY**  
**FOR MOUNTAIN CONTOUR PLANTING TO ANY CONTOUR SAFE FOR**  
**PRIME MOVER · OPERATES WITH TWO HYDRAULIC CYLINDERS**  
**PRICE: \$ 9,100.00.00 F.O.B. MABLETON, GEORGIA ♦ USA**

MODEL 'SC' SINGLE CRANK AXLE CAN BE CHANGED TO OPERATE AS A DOUBLE CRANK AXLE  
OR MODEL 'DC' DOUBLE CRANK AXLE CAN BE CHANGED TO OPERATE AS A SINGLE CRANK  
AXLE BY ADDING OR OMITTING CERTAIN PARTS · FURTHER DETAILS UPON REQUEST AS  
NEEDED

**CRANK AXLE EQUIPPED PLANTERS ARE FOR FIELD, DOZER & WILDLAND**  
**PLANTING · NOT FOR BEDDED LAND WHICH REQUIRES 3 PT. HITCH**  
**STANDARD SPECIFICATIONS EITHER UNIT**

- CONSTRUCTED OF 1/2" X 4" X 6" STRUCTURAL TUBING · AXLE SHAFT 3" OD
- CARRIER LEGS SOLID 4" X 6" PLATE ➤ 3/4" X 4" A-FRAME ➤ THREE DIFFERENT CYLINDER POSITIONS ➤ 1-15/16" SHAFT TO ATTACH PLANTER, SUBSOILER OR OTHER UNIT TO AXLE
- EQUIPPED WITH DOUBLE-ACTING CYLINDER WITH 2" ROD X 4" BORE X 12" STROKE, ALL HYDRAULIC HOSES NECESSARY FOR OPERATION · SUPPLIED WITH CYLINDER LOCK
- HEAVY DUTY 1-3/4" REPLACEABLE AXLE SPINDLES · TIMKEN EQUIPPED
- HIGH-FLOTATION 11L X 15 8-PLY TIRES · REINFORCED RIMS AND VALVE PROTECTORS
- SWIVEL BRACKET FOR ATTACHMENT TO PRIME MOVER · HEIGHT OF SWIVEL BRACKET NOT TO EXCEED 14" FROM GROUND LEVEL WHEN IN USE · THE HIGHER THE ATTACHMENT POINT, THE LESS DRAFT THE PLANTER HAS GOING INTO SOIL OR CUTTING DEBRIS IN TWO
- NOT SUPPLIED HYDRAULIC QUICK DISCONNECTS AND PIN FOR ATTACHING TO TRACTOR



**INFORMATION FOR FLATBED TRUCK SHIPPING:**

**EITHER UNIT: 9' LONG X 7' WIDE X 4' HIGH**

**SINGLE CRANK AXLE WEIGHT: 2000 LB. · DOUBLE CRANK AXLE WEIGHT: 2300 LB.**